



Trulink[®] 4-Port VGA/USB 2.0 KVM Switch

- Supports video resolutions up to 2048 x 1536 pixels
- Supports Microsoft[®] Windows[®] (98, 98SE, 2000, ME[®], XP, Vista,7), Mac[®] OS 9/X, Linux, and Sun[®] Micro OS
- Features autoscan and autoswitch
- Offers overcurrent protection
- Compatible with USB 2.0 specification Deep Color

Specifications: Trulink® 4-Port VGA/USB 2.0 KVM Switch

Signal Specifications:

Video Signal Supported:	VGA
Maximum Resolution Supported:	2048 x 1536
USB Specification Supported:	USB 2.0
Audio Signal Support (35568 only):	Stereo Audio
Switching Methods:	Keyboard Hotkeys Push button Auto-Scan

Power Adapter Specifications

Power Input:	100-240V 50/60Hz, 0.4A
Power Output:	5V, 2.0A
Power Cable Length:	5ft
Power Pin Diameter:	5.5mm
Center Pin Polarity:	Positive

Physical Characteristics:

Number of Computers Supported:	4
Computer Connection Ports:	HD15 (VGA) Male x 4 USB B Female x 4 3.5mm Female x 8 (35568 only)
Console Ports:	HD15 VGA Female x 1 USB A Female x 2 (keyboard and mouse) 3.5mm Female x 2 (35568 only)
USB Hub:	USB A Female x 2
Included Cables:	HD15 (VGA) M/F and USB A to B Combo Cable x 4 Dual 3.5mm cable x 2 (35568 only)
Cable Length:	1.8m
Housing Material:	Metal
Dimensions:	7.9 x 3.2 x 1.7in

Part Number	Description	Weight (lbs)
2006-35567-000	Trulink® 4-Port VGA/USB 2.0 KVM Switch	5.224
2006-35568-000	Trulink® 4-Port VGA/USB 2.0 KVM Switch with Audio	5.864